



WHISPER AIR

Enjoy the silence.

2VV product presentation

Enjoy the silence.

WHISPER AIR

Compact decentralized HRU



AIR HEATERS
HANDLING UNITS
HEAT RECOVERY UNITS
HVAC COMPONENTS

AIR CURTAINS
HEATERS
HANDLING UNITS
HEAT RECOVERY UNITS
AIR CURTAINS

HEATERS
HANDLING UNITS
HEAT RECOVERY UNITS
HVAC COMPONENTS

AIR CURTAINS
HEATERS
HANDLING UNITS
HEAT RECOVERY UNITS
AIR CURTAINS


HEATERS
HANDLING UNITS
HEAT RECOVERY UNITS
AIR CURTAINS

Enjoy the silence.

WHISPER AIR

Applications

- Class rooms
- Conference rooms
- Offices



AIR HEATERS
HANDLING UNITS
HEAT RECOVERY UNITS
HVAC COMPONENTS
AIR CURTAINS HEATERS
HANDLING UNITS
HEAT RECOVERY UNITS
AIR CURTAINS HEATERS
HANDLING UNITS
HEAT RECOVERY UNITS

WHISPER AIR

Technical parameters

- **3 sizes according to nominal air volume:**
 - Size 400 (boost: 700)
 - Size 700 (boost: 900)
 - Size 1000 (boost: 1400)
- Electric preheater
- Electric post heater
- Water post heater




AIR HEATERS
HANDLING UNITS
HEAT RECOVERY UNITS
HVAC COMPONENTS
AIR CURTAINS HEATERS
HANDLING UNITS
HEAT RECOVERY UNITS
AIR CURTAINS HEATERS
HANDLING UNITS
HEAT RECOVERY UNITS
AIR CURTAINS HEATERS
HANDLING UNITS
HEAT RECOVERY UNITS
HVAC COMPONENTS
AIR CURTAINS HEATERS
HANDLING UNITS
HEAT RECOVERY UNITS
AIR CURTAINS HEATERS
HANDLING UNITS
HEAT RECOVERY UNITS
AIR CURTAINS HEATERS
HANDLING UNITS
HEAT RECOVERY UNITS

WHISPER AIR

Technical parameters

Silent operation

- Max. $L_{PA1m} = 35$ dB at nominal air flow
- Special configuration of components
- Acoustic insulation (casing, bottom panel)
- Low internal pressure losses and air velocities
- Labyrinthine & honeycomb attenuators



AIR HEATERS
HANDLING UNITS
HEAT RECOVERY UNITS
HVAC COMPONENTS
AIR CURTAINS HEATERS
HANDLING UNITS
HEAT RECOVERY UNITS
AIR CURTAINS HEATERS
HANDLING UNITS
HEAT RECOVERY UNITS
HVAC COMPONENTS
AIR CURTAINS HEATERS
HANDLING UNITS
HEAT RECOVERY UNITS
AIR CURTAINS HEATERS
HANDLING UNITS
HEAT RECOVERY UNITS
HVAC COMPONENTS
AIR CURTAINS HEATERS
HANDLING UNITS
HEAT RECOVERY UNITS
AIR CURTAINS HEATERS
HANDLING UNITS
HEAT RECOVERY UNITS
HVAC COMPONENTS
AIR CURTAINS HEATERS
HANDLING UNITS
HEAT RECOVERY UNITS
AIR CURTAINS HEATERS
HANDLING UNITS
HEAT RECOVERY UNITS
HVAC COMPONENTS

WHISPER AIR

Technical parameters

Energy efficient

- EC fans
- Heat recovery
 - Aluminium plate counter-flow heat exchanger
 - Min. dry thermal efficiency 80% (EN 308)
 - Fluent by-pass 0-100%
- Filters
 - F7/G4
 - Large surface
 - Clogging indicated by direct measurement of pressure difference

ebmpapst



AIR HEATERS
HANDLING UNITS
HEAT RECOVERY
HVAC COMPONENTS

AIR CURTAINS HEATERS
HANDLING UNITS
HEAT RECOVERY


Enjoy the silence.



WHISPER AIR

Heat recovery


- Thermal efficiency diagram



AIR HEATERS
HANDLING
HEAT RECOVERY
HVAC COMPONENTS
AIR CURTAINS
HEATERS
HANDLING
HEAT RECOVERY
AIR CURTAINS
HEATERS
HANDLING
HEAT RECOVERY

WHISPER AIR

Principle



	EN
1	Fan
2	Filter
3	Preheater
4	Afterheater
5	Condensate drain
6	Heat exchanger with by-pass damper
7	Straw system



AIR HEATERS
HANDLING UNITS
HEAT RECOVERY UNITS
HVAC COMPONENTS
AIR CURTAINS HEATERS
HANDLING UNITS
HEAT RECOVERY UNITS
AIR CURTAINS HEATERS
HANDLING UNITS
HEAT RECOVERY UNITS

WHISPER AIR

Installation & Maintenance

- Compact Plug&Play unit
- Exposed or semi-recessed installation
- Aluminium casing -> low weight
- Wall frame available as accessory
- Easy access – bottom panel on hinges





AIR HEATERS
HANDLING UNITS
HEAT RECOVERY HVAC COMPONENTS
AIR CURTAINS HEATERS
HANDLING UNITS
HEAT RECOVERY
AIR CURTAINS HEATERS
HANDLING UNITS
HEAT RECOVERY

Enjoy the silence.

WHISPER AIR

Straw system

- Performing laminar airflow
- Maximizing air throw distance



AIR HEATERS
HANDLING UNITS
HEAT RECOVERY UNITS
HVAC COMPONENTS
AIR CURTAINS HEATERS
HANDLING UNITS
HEAT RECOVERY UNITS
AIR CURTAINS HEATERS
HANDLING UNITS
HEAT RECOVERY UNITS
HVAC COMPONENTS
AIR CURTAINS HEATERS
HANDLING UNITS
HEAT RECOVERY UNITS
AIR CURTAINS HEATERS
HANDLING UNITS
HEAT RECOVERY UNITS
AIR CURTAINS HEATERS
HANDLING UNITS
HEAT RECOVERY UNITS

WHISPER AIR

Preheater

- Electric

- 1,5kW
- 2,0kW
- 3,0kW




Post heater



- Electric

- 1,5kW
- 2,25kW
- 3,0kW



- Water




AIR HEATERS
HANDLING UNITS
HEAT RECOVERY UNITS
HVAC COMPONENTS
AIR CURTAINS HEATERS
HANDLING UNITS
HEAT RECOVERY UNITS
AIR CURTAINS HEATERS
HANDLING UNITS
HEAT RECOVERY UNITS

Enjoy the silence.



WHISPER AIR

Air velocity simulation




AIR HEATERS
HANDLING
HEAT RECOVERY
HVAC COMPONENTS
AIR CURTAINS
HEATERS
HANDLING
HEAT RECOVERY
AIR CURTAINS
HEATERS
HANDLING
HEAT RECOVERY

WHISPER AIR

Air velocity simulation


- Ideal position of unit = middle of longer wall
-> equal air distribution at low velocities + Coanda effect



WHISPER AIR

Air velocity simulation

- Ideal position of unit = middle of longer wall
-> equal air distribution at low velocities + Coanda effect



AIR HEATERS
HANDLING UNITS
HEAT RECOVERY
HVAC COMPONENTS
AIR CURTAINS HEATERS
HANDLING UNITS
HEAT RECOVERY
AIR CURTAINS HEATERS
HANDLING UNITS
HEAT RECOVERY
HVAC COMPONENTS
AIR CURTAINS HEATERS
HANDLING UNITS
HEAT RECOVERY
AIR CURTAINS HEATERS
HANDLING UNITS
HEAT RECOVERY
AIR CURTAINS HEATERS
HANDLING UNITS
HEAT RECOVERY

Enjoy the silence.

WHISPER AIR

Control Comfort

- Design controller with touch-screen display
- CO₂ sensor inbuilt (DCV)
- Fluent fan and heaters control
- Clogged filters indication (pressure loss measurement)
- Boost regime
- Fluent by-pass
 - Anti-freeze protection
 - Temperature control (freecooling)
- Integrated timer (week, day)
- Option for BMS control (ModBUS RTU)




AIR HEATERS
HANDLING UNITS
HEAT RECOVERY UNITS
HVAC COMPONENTS
AIR CURTAINS HEATERS
HANDLING UNITS
HEAT RECOVERY UNITS
AIR CURTAINS HEATERS
HANDLING UNITS
HEAT RECOVERY UNITS
HVAC COMPONENTS
AIR CURTAINS HEATERS
HANDLING UNITS
HEAT RECOVERY UNITS
AIR CURTAINS HEATERS
HANDLING UNITS
HEAT RECOVERY UNITS
AIR CURTAINS HEATERS
HANDLING UNITS
HEAT RECOVERY UNITS

WHISPER AIR

Dimensions

- Size 400: W=1875mm, L=990 mm, H=400 mm, D= 250 mm
- Size 700: W=2145 mm, L=1160 mm, H=455 mm, D=315 mm
- Size 1000: W=2475 mm, L=1315 mm, H=570 mm, D=315 mm



AIR HEATERS
HANDLING UNITS
HEAT RECOVERY UNITS
HVAC COMPONENTS
AIR CURTAINS HEATERS
HANDLING UNITS
HEAT RECOVERY UNITS
AIR CURTAINS HEATERS
HANDLING UNITS
HEAT RECOVERY UNITS
HVAC COMPONENTS
AIR CURTAINS HEATERS
HANDLING UNITS
HEAT RECOVERY UNITS
AIR CURTAINS HEATERS
HANDLING UNITS
HEAT RECOVERY UNITS
AIR CURTAINS HEATERS
HANDLING UNITS
HEAT RECOVERY UNITS

WHISPER AIR

Summary


- Ecodesign 2018 compliance
- High efficiency
- **Ultra quiet operation ($L_{PA1m} = 35 \text{ dB}$)**
 - Confirmed by accredited testing lab
- Option for integrated preheater and post heater
- Easy installation and maintenance
- Modern control system with touch-screen display

Etelab



AIR HEATERS
HANDLING UNITS
HEAT RECOVERY
HVAC COMPONENTS
AIR CURTAINS HEATERS
HANDLING UNITS
HEAT RECOVERY
AIR CURTAINS HEATERS
HANDLING UNITS
HEAT RECOVERY
HVAC COMPONENTS
AIR CURTAINS HEATERS
HANDLING UNITS
HEAT RECOVERY
AIR CURTAINS HEATERS
HANDLING UNITS
HEAT RECOVERY

Enjoy the silence.



Thank you for your attention!

Copyright © 2VV s.r.o., all rights reserved